

IGBT MODULE (L series)

■ Features

- High Speed Switching
- Low Saturation Voltage
- Voltage Drive

■ Applications

- Inverter for Motor Drive
- AC and DC Servo Drive Amplifier
- Uninterruptible Power Supply
- Industrial Machines, such as Welding Machines

■ Maximum Ratings and Characteristics

● Absolute Maximum Ratings

Items		Symbols	Ratings	Units
Collector-Emitter Voltage		V_{CES}	600	V
Gate-Emitter Voltage		V_{GES}	± 20	V
Collector Current	Continuous	I_C	20	A
	1ms	$I_{C\ pulse}$	40	
	Continuous	$-I_C$	20	
	1ms	$-I_{C\ pulse}$	40	
Max. Power Dissipation		P_C	80	W
Operating Temperature		T_j	+150	°C
Storage Temperature		T_{stg}	-40 to +125	°C
Net. Weight			150	g
Isolation Voltage	AC. 1min.	V_{isol}	2500	V
Screw Torque		Mounting *1	35	kg·cm

*1 Recommendable Value 25 to 35kg·cm (M5)

● Electrical Characteristics ($T_j=25^\circ\text{C}$)

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	I_{CES}	$V_{GE}=0V$ $V_{CE}=600V$ $T_j=25^\circ\text{C}$			1.0	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}=0V$ $V_{GE}=\pm 20V$			100	nA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{CE}=20V$ $I_C=20mA$	3.0	4.5	6.0	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V$ $I_C=20A$		2.7	3.5	V
Input Capacitance	C_{ies}	$V_{GE}=0V$		1900		pF
Output Capacitance	C_{oes}	$V_{CE}=10V$		—		
Reverse Transfer Capacitance	C_{res}	$f=1MHz$		—		
Turn-on Time *2	t_{on}	$V_{CC}=300V$		0.4	0.8	μs
	t_r	$I_C=20A$		0.3	0.6	
Turn-off Time *3	t_{off}	$V_{GE}=\pm 15V$		0.6	1.0	
	t_f	$R_G=120\Omega$		0.2	0.35	
Diode Forward On-Voltage	V_F	$I_F=20A$ $V_{GE}=0V$			2.5	V
Reverse Recovery Time	t_{rr}	$I_F=20A$ $-di/dt=100A/\mu\text{s}$ $V_{GE}=-10V$			300	ns


*2 Resistive load

*3 Inductive load


● Thermal Characteristics


Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	$R_{th(j-c)}$	IGBT			1.56	°C/W
	$R_{th(j-e)}$	Diode			3.01	
	$R_{th(c-f)}$	With Thermal compound		0.06		

■ Outline Drawings




■ Equilavelent Circuit Schematic







Collector Current vs. Collector-Emitter Voltage




Collector-Emitter Voltage vs. Gate-Emitter Voltage




Switching Time







Switching Time-Gate Resistance



Dynamic Input Characteristic



Forward Voltage of Free Wheel Diode



For more information, contact:

Collmer Semiconductor, Inc.

P.O. Box 702708

Dallas, TX 75370

972-733-1700

972-381-9991 Fax

<http://www.collmer.com>