

SPECIFICATION

Device Name : IGBT Module

Type Name : 7MBR50SA060-01

Spec. No. : MS6M 0544

Date : Jun. - 02 - 2000

Fuji Electric Co.,Ltd.
Matsumoto Factory

DATE		NAME	APPROVED	Fuji Electric Co.,Ltd.		
DRAWN	Jun. - 2 - 00	J. Kikuyasu	J. Kikuyasu	DWG. NO.	MS6M 0544	1 / 10
CHECKED	June - 2 - 00	S. Kikuyasu				

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

Revised Records

[illegible]

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

Fuji Electric Co., Ltd.

DWG.NO.


MS6M 0544

$$\frac{2}{10}$$


H04-004-06

7MBR50SA060-01

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



Fuji Electric Co., Ltd.

DWG NO

MS6M 0544

3/10

H04-004-03

3. Absolute Maximum Ratings (at Tc= 25C unless otherwise specified)

Items		Symbols	Conditions	Maximum Ratings	Units
Inverter	Collector-Emitter voltage	VCES		600	V
	Gate-Emitter voltage	VGES		+20	V
	Collector current	Ic	Continuous	50	A
		Icp	1ms	100	A
		-Ic		50	A
	Collector Power Dissipation	Pc	1 device	200	W
Brake	Collector-Emitter voltage	VCES		600	V
	Gate-Emitter voltage	VGES		+20	V
	Collector current	Ic	Continuous	30	A
		Icp	1ms	60	A
	Collector Power Dissipation	Pc	1 device	120	W
	Repetitive peak reverse Voltage(Diode)	VRRM		600	V
Converter	Repetitive peak reverse Voltage	VRRM		800	V
	Average Output Current	Io	50Hz/60Hz sine wave	50	A
	Surge Current (Non-Repetitive)	IFSM	Tj=150C,10ms	350	A
	I ² t (Non-Repetitive)	I ² t	half sine wave	613	A ² s
Junction temperature		Tj		150	C
Storage temperature		Tstg		-40~ +125	C
Isolation voltage	between terminal and copper base ^{(*)1}	Viso	AC : 1min.	2500	V
	between thermistor and others ^{(*)2}			2500	V
Mounting Screw Torque ^{(*)3}				3.5	Nm

(*)1 All terminals should be connected together when isolation test will be done.

(*)2 Terminal 8 and 9 should be connected together. Terminal 1 to 7 and 10 to 24 should be connected together and shorted to copper base.

(*)3 Recommendable Value : 2.5~3.5 Nm (M5)

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

4. Electrical characteristics (at $T_j = 25^\circ\text{C}$ unless otherwise specified)


Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Inverter	Zero gate voltage Collector current	ICES VGE 0 V, VCE 600 V			1.0	mA
	Gate-Emitter leakage current	IGES VCE 0 V, VGE ± 20 V			200	nA
	Gate-Emitter threshold voltage	VGE(th) VCE 20 V, $I_c = 50$ m	5.5	7.8	8.5	V
	Collector-Emitter saturation voltage	VCE(sat) VGE 15 V, chip		1.8		V
		$I_c = 50$ A terminal		1.95	2.4	
	Input capacitance	Cies VGE 0 V, VCE 10 V $f = 1$ MHz		5000		pF
	Turn-on time	Vcc= 300 V $I_c = 50$ A VGE ± 15 V		0.45	1.2	us
				0.25	0.6	
				0.08		
	Turn-off time	RG = 51 ohm		0.40	1.0	
				0.05	0.35	
Brake	Forward on voltage	VF IF = 50 A chip		1.75		V
		terminal		1.9	2.6	
	Reverse recovery time	trr IF = 50 A			300	ns
	Zero gate voltage Collector current	ICES VGE 0 V, VCE 600 V			1.0	mA
	Gate-Emitter leakage current	IGES VCE 0 V, VGE ± 20 V			200	nA
	Collector-Emitter saturation voltage	VCE(sat) VGE 15 V, chip		1.8		V
		$I_c = 30$ A terminal		1.95	2.4	
	Turn-on time	Vcc= 300 V $I_c = 30$ A		0.45	1.2	us
				0.25	0.6	
	Turn-off time	VGE ± 15 V RG = 82 ohm		0.40	1.0	
				0.05	0.35	
Converter	Reverse current	IRRM VR = 600 V			1.0	mA
	Forward on voltage	VFM IF = 50 A chip		1.1		V
		terminal		1.2	1.5	
Thermistor	Reverse current	IRRM VR = 800 V			1.0	mA
	Resistance	R T = 25°C		5000		ohm
		T = 100°C	465	495	520	
	B value	B T = 25/50°C	3305	3375	3450	K

5. Thermal resistance characteristics

Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Thermal resistance (1 device)	Rth(j-c)	Inverter IGBT			0.63	C/W
		Inverter FWD			1.33	
		Brake IGBT			1.04	
		Converter Diode			2.42	
Contact Thermal resistance	Rth(c-f)	with Thermal Compound (*)		0.05		C/W

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

6. Indication on module




7. Applicable category

This specification is applied to Power Integrated Module named 7MBR50SA060-01.







8. Storage and transportation notes

- The module should be stored at a standard temperature of 5 to 35°C and humidity of 45 to 75% .
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
- Avoid exposure to corrosive gases and dust.
- Avoid excessive external force on the module.
- Store modules with unprocessed terminals.
- Do not drop or otherwise shock the modules when transporting.
- Please connect adequate fuse or protector of circuit between three-phase line and this product to prevent the equipment from causing secondary destruction.







9. Definitions of switching time








This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.









This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party without the express written consent of Fuji Electric Co., Ltd.



This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.



This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.



Fuji Electric Co., Ltd.

DWG. NO.

MS6M 0544

10/10

H04-004-03